



# GV Lawn

## USES

- ▶ Landscape
- ▶ Lawns
- ▶ Traffic Medians
- ▶ Pet Areas
- ▶ Commercial or Residential
- ▶ Light-Heavy Traffic
- ▶ Multi-Use Activity Areas



15 Year Manufacturer's Warranty

8 Year Manufacturer's High Traffic Warranty



Flo-Rite Drainage Technology



## SPECIFICATIONS

Pile Height: 1-½"

Turf Gauge: 3/8"

Face Weight: 51 oz./ yd<sup>2</sup>

Backing Weight: 23 oz./yd<sup>2</sup>

Total Weight: 74 oz./yd<sup>2</sup>

Stitch Rate: 15/10 cm

Stitches/m<sup>2</sup>: 15,750

Material/Dtex: PE 9000 & PP 4000

Color : Field Green & Olive Green with Brown and Green Thatching

Type Of Fiber: PE Monofilament and PP Curled Thatch

Infill Amount: 2.0 lb./psf.

Primary Backing: Premium GST Backing

Tuft Bind: 14+ lbs/force (ASTM D1335)

Permeability: 84.6 inches/hr. (ASTM F1551)

Melting Point: 150 °F (ASTM D2859)

Grab Tear MD: > 200 lbs/force (ASTM D5034)

Grab Tear CMD: > 170 lbs/force (ASTM D5034)

Roll Width: 15 ft

Roll Length: 100 ft

Sq. Ft. Per Roll: 1500

Total Roll Weight: 790 lbs

