



GV Pet

USES

- ▶ General Landscape
- ▶ Lawns
- ▶ Pet Areas
- ▶ Roof Decks
- ▶ Medians
- ▶ Commercial or Residential



15 Year Manufacturer's Warranty

8 Year Manufacturer's High Traffic Warranty



Flo-Rite Drainage Technology



SPECIFICATIONS

Pile Height: 1.125"

Turf Gauge: 3/8"

Face Weight: 55 oz./ yd²

Backing Weight: 26 oz./yd²

Total Weight: 71 oz./yd²

Stitch Rate: 20.5/10 cm

Stitches/m²: 11,525

Material/Dtex: PE & PP 14,400

Color: Field, Apple Face with Green and Tan Thatch

Type Of Fiber: PE Monofilament and PP Curled Thatch

Infill Amount: 1.5 lb./psf.

Primary Backing: Premium AST Backing

Tuft Bind: 6+ lbs/force (ASTM D1335)

Permeability: 96.1 inches/hr. (ASTM F1551)

Melting Point: 150 °F (ASTM D2859)

Grab Tear MD: > 200 lbs/force (ASTM D5034)

Grab Tear CMD: > 200 lbs/force (ASTM D5034)

Roll Width: 15 ft

Roll Length: 100 ft

Sq. Ft. Per Roll: 1500

Total Roll Weight: 845 lbs

