



GV Prestige

USES

- ▶ General Landscape
- ▶ Lawns
- ▶ Pet Areas
- ▶ Roof Decks
- ▶ Medians
- ▶ Multi-Use Activity Areas.



15 Year Manufacturer's Warranty

8 Year Manufacturer's High Traffic Warranty



Flo-Rite Drainage Technology



SPECIFICATIONS

Pile Height: 1.75"

Turf Gauge: 3/8"

Face Weight: 60 oz./yd²

Backing Weight: 26 oz./yd²

Total Weight: 86 oz./yd²

Stitch Rate: 11/10cm

Stitches/m²: 11,550

Material/Dtex: PE & PP 14,400

Color: Field, Olive, Tan and Emerald Face Blades with Tan and Green Thatch

Type Of Fiber: PE Monofilament and PP Curled As Thatch

Infill Amount: 2.0 lb./psf.

Primary Backing: Premium AST Backing

Tuft Bind: 15.3 lbs/force (ASTM D1335)

Permeability: 122.3 inches/hr. (ASTM F1551)

Melting Point: 150°F (ASTM D2859)

Grab Tear MD: 229.0 lbs/force (ASTM D5034)

Grab Tear CMD: 285.7 lbs/force (ASTM D5034)

Roll Width: 15 ft

Roll Length: 100 ft

Sq. Ft. Per Roll: 1,500

Total Roll Weight: 945 lbs

