



GV Supreme

Note: This product has limited availability.
Currently available in Arizona & Las Vegas, NV only.

USES

- ▶ Landscape
- ▶ Lawns
- ▶ Playgrounds
- ▶ Traffic Medians
- ▶ Pet Areas
- ▶ Commercial or Residential
- ▶ Light-Heavy Traffic



15 Year Manufacturer's Warranty
8 Year Manufacturer's High Traffic Warranty



Flo-Rite Drainage Technology



SPECIFICATIONS

Pile Height: 1¾"

Turf Gauge: ½"

Face Weight: 66 oz./ yd²

Backing Weight: 27 oz./yd²

Total Weight: 93 oz./yd²

Stitch Rate: 20/10 cm

Stitches/m²: 13,860

Material/Dtex: PE 10000 & PP 4000

Color : Emerald Green & Olive Green with Brown and Green Thatching

Type Of Fiber: PE Monofilament and PP Curled As Thatch

Infill Amount: 2.0 lb./psf.

Primary Backing: Premium GST Backing

Tuft Bind: 13+ lbs/force (ASTM D1335)

Blade Type: S Shape Blade

Permeability: 122.6 inches/hr. (ASTM F1551)

Melting Point: 176 °F (ASTM D2859)

Grab Tear MD: > 200 lbs/force (ASTM D5034)

Grab Tear CMD: > 200 lbs/force (ASTM D5034)

Roll Width: 15 ft

Roll Length: 75ft, 100 ft

Sq. Ft. Per Roll: 1,125, 1,500

Total Roll Weight: 927 lbs

